

## **Nusku Fireblocker : Standard Product Guide**

**Board & Battens Collection:** Page 2

**Tongue & Groove Collection:** Page 3

**Bevels Collection:** Page 4

**Shiplap Collection:** Page 5

**Lap Siding Collection:** Page 6

## **Nusku Fireblocker Standard Patterns**

At Weaverbird there are many profiles that we consider standard to our daily operators & clients usage. These are typically the most versatile profiles that have the broadest range of installation options.

## **Nusku Fireblocker Custom Patterns**

A huge benefit of Weaverbird is our ability to tailor a solution outside our standard offering. We develop CAD drawings internally that are specific to a project/client requirements & then mill & finish to provide a truly customized material.



**WEAVERBIRD**

[weaverbirdco.com](http://weaverbirdco.com)

[hello@weaverbirdco.com](mailto:hello@weaverbirdco.com)

showroom : 2732 east coast highway  
corona del mar, ca 92625



## Applications

The Boards Collection allows significant creativity & flexibility from an installation perspective. These standard profiles can be used for siding, trim, fascia, belly band & other areas where a pre-primed millwork component adds value.

1x S1S2E (1/8" R : Resawn Back)					
<p>1x4 Example</p>	1x4	1x6	1x8	1x10	1x12
	.6875 x 3.5	.6875 x 5.5	.6875 x 7.25	.6875 x 9.25	.6875 x 11.25

\*All 1x boards are available in 16' & 20' Lengths : 1x2, 1x3 & 1x14 also available with special order

5/4x S1S2E (1/8" R : Resawn Back)					
<p>5/4x4 Example</p>	5/4x4	5/4x6	5/4x8	5/4x10	5/4x12
	1.0 x 3.5	1.0 x 5.5	1.0 x 7.25	1.0 x 9.25	1.0 x 11.25

\*All 5/4x boards are available in 16' Length Only

2x S1S2E (1/8" R : Resawn Back)					
<p>2x4 Example</p>	2x4	2x6	2x8	2x10	2x12
	1.5 x 3.5	1.5 x 5.5	1.5 x 7.25	1.5 x 9.25	1.5 x 11.25

\*All 2x boards are available in 16' & 20' Lengths : 2x2, 2x3 & 2x14 also available with special order

## Installation

With S1S2E Boards, material has to be face fastened with SS nails. No 316 Stainless steel ring shank siding nail are recommended and require 1-1/4" penetration into solid nailable substrate. Pre-drill to avoid splitting if less than 2" from the edge. Fastened 16" O/C for double nail.

Nominal Width	x2	x3	x4	x6	x8	x10	x12
Nails Per Stud	1 Nail	1 Nail	2 Nails	2 Nails	2 Nails	3 Nails	3 Nails

## Finishing

Fireblocker is delivered factory primed & requires minimum 2 coats of high quality, 100% acrylic latex exterior paint as soon as possible after installation. Apply paint according to manufacturer's recommended spread rates & coats. Brush application ensures best coverage & protection.





### Applications

The Tongue & Groove collection can be used in applications like siding, soffits, accent walls, interior/exterior ceilings and other areas hoping to hide the fastener during install.

1x T&G Reversible #709R, #711R, #712R & #713R (1/4 V-Groove : 1/2" Reveal)				
	1x4 (#709R)	1x6 (#711R)	1x8 (#712R)	1x10 (#713R)
	.6875 x 3.375	.6875 x 5.375	.6875 x 7.125	.6875 x 9.125

\*All T&G Reversible available in 16' & 20' Lengths

1x T&G Edge & Center Bead (Butt Joint Back)		
	1x4	1x6
	.6875 x 3.375	.6875 x 5.375

\*All Edge & Center Bead available in 16' Length Only

1x T&G Finline (3/16" Square Channel : Single Face)			
	1x4	1x6	1x8
	.6875 x 3.375	.6875 x 5.375	.6875 x 7.125

\*All T&G Finline available in 16' & 20' Lengths

### Installation

With T&G, material can be face or blind fastened with SS nails. No 316 Stainless steel ring shank siding nail are recommended and require 1-1/4" penetration into solid nailable substrate. Pre-drill to avoid splitting if less than 2" from the edge. Fastened 16" O/C for double nail.

Nominal Width	x2	x3	x4	x6	x8	x10	x12
Nails Per Stud	1 Nail	1 Nail	1 Nails	1 Nails	2 Nails	3 Nails	3 Nails

### Finishing


Fireblocker is delivered factory primed & requires minimum 2 coats of high quality, 100% acrylic latex exterior paint as soon as possible after installation. Apply paint according to manufacturer's recommended spread rates & coats. Brush application ensures best coverage & protection.






## Applications


The Bevel collection is almost exclusively used for exterior siding & accent walls but can easily be used interior if the design requires.

1/2x Rab Bevel #400	
 <p>1/2x4 Example</p>	1x4 (#400)
	.4375 x 3.5

\*All Pattern #400 is available in 16' Length only

1/2x Rab Bevel #362 & #363		
 <p>1/2x6 Example</p>	1x6 (#362)	1x8 (#363)
	.4375 x 5.375	.4375 x 7.25

\*All Pattern #362 & #363 is available in 16' Length only

3/4x Rab Bevel #371, #372 & #373			
 <p>3/4x6 Example</p>	3/4x6 (#371)	3/4x8 (#372)	3/4x10 (#373)
	.6875 x 5.5	.6875 x 7.25	.6875 x 9.25

\*All 3/4x Rab Bevel Patterns are available in 16' & 20' Lengths

## Installation

With Bevels, material has to be face fastened with SS nails. No 316 Stainless steel ring shank siding nail are recommended and require 1-1/4" penetration into solid nailable substrate. Pre-drill to avoid splitting if less than 2" from the edge. Fastened 16" O/C for double nail.

Nominal Width	x2	x3	x4	x6	x8	x10	x12
Nails Per Stud	1 Nail	1 Nail	1 Nails	1 Nails	2 Nails	3 Nails	3 Nails

## Finishing

Fireblocker is delivered factory primed & requires minimum 2 coats of high quality, 100% acrylic latex exterior paint as soon as possible after installation. Apply paint according to manufacturer's recommended spread rates & coats. Brush application ensures best coverage & protection.





## Applications

The Shiplap collection can be used in applications like siding, soffits, accent walls, interior/exterior ceilings where craftsman style siding appearance is desired.

1x WP-11R Reversible			
	1x6 (WP-11R)	1x8 (WP-11R)	1x10 (WP-11R)
	.6875 x 5.375	.6875 x 7.125	.6875 x 9.125

\*All WP-11R is available in 16' & 20' Lengths

1x Bevel Channel Shiplap #773			
	1x6 (#773)	1x8 (#773)	1x10 (#773)
	.6875 x 5.5	.6875 x 7.5	.6875 x 9.5

\*All Bevel Channel Shiplap is available in 16' & 20' Lengths

1x Cove Channel Shiplap #770, #771, #772			
	1x6 (#770)	1x8 (#771)	1x10 (#772)
	.6875 x 5.5	.6875 x 7.5	.6875 x 9.5

\*All Cove Channel Shiplap is available in 16' & 20' Lengths

## Installation

With Shiplaps, material has to be face fastened with SS nails. No 316 Stainless steel ring shank siding nail are recommended and require 1-1/4" penetration into solid nailable substrate. Pre-drill to avoid splitting if less than 2" from the edge. Fastened 16" O/C for double nail.

Nominal Width	x2	x3	x4	x6	x8	x10	x12
Nails Per Stud	1 Nail	1 Nail	2 Nails	2 Nails	2 Nails	3 Nails	3 Nails

## Finishing


Fireblocker is delivered factory primed & requires minimum 2 coats of high quality, 100% acrylic latex exterior paint as soon as possible after installation. Apply paint according to manufacturer's recommended spread rates & coats. Brush application ensures best coverage & protection.





## Applications

The Lap Siding collection is almost exclusively used for exterior siding & accent walls but can easily be used interior if the design requires.

1x 2-Lap Drop Siding #430 & #431		
1x8 Example 	1x6 (#430)	1x8 (#431)
	.6875 x 5.5	.6875 x 7.5

\*All 2-Lap Siding available in 16' & 20' Lengths

1x 3-Lap Drop Siding #432 & #433		
1x8 Example 	1x8 (#432)	1x10 (#433)
	.6875 x 7.5	.6875 x 9.5

\*All 3-Lap Siding available in 16' & 20' Lengths

## Installation

With Lap Siding, material has to be face fastened with SS nails. No 316 Stainless steel ring shank siding nail are recommended and require 1-1/4" penetration into solid nailable substrate. Pre-drill to avoid splitting if less than 2" from the edge. Fastened 16" O/C for double nail.

Nominal Width	x2	x3	x4	x6	x8	x10	x12
Nails Per Stud	1 Nail	1 Nail	2 Nails	2 Nails	2 Nails	3 Nails	3 Nails

## Finishing

Fireblocker is delivered factory primed & requires minimum 2 coats of high quality, 100% acrylic latex exterior paint as soon as possible after installation. Apply paint according to manufacturer's recommended spread rates & coats. Brush application ensures best coverage & protection.

